

KP CM1260

Every step in the histopathology and cytology lab requires the utmost attention. Regardless of the certification of your lab and the number of QA people, a clear coverslip result, without any distractions, is highly important to be able to examine the slide for a reliable diagnoses.



www.klinipath.com

KLINIPATH's latest development in coverslipping is the new CM1260 automated tape coverslipper. A simplified, reliable and low-maintenance instrument. Special features such as a multilingual operating touchscreen (English, German, French, Spanish, Dutch), adjustable settings for the length of the tape between the range of 45 and 70 mm. and accurate dosage of the necessary xylene. Equipped with a self sharpening knife, a sensor controlled coverslipping process combined with a 3X glass coverslipper capacity, the CM1260 is the future in coverslipping.



multilingual touch screen
parameter setting



slide drying
excessive xylene collection



high output



simple and easy operation
clear results

KLINIPATH's KP-Tape is a world-wide accepted product for use in coverslipping. From Finland to Australia, from Canada to Taiwan, laboratories all over the world are using KP-Tape with excellent results.

With over 10 years of experience, laboratories have perfect coverslipped slides, even in long term storage.

Independent market research in The Netherlands has proven that KP-Tape is an extremely reliable product. A copy of this study is available from your local supplier.



S P E C I F I C A T I O N S

Product no.	CM1260
Product	Automated Tape Coverslipper
Maximum output	1260 slides per hour
Slide dimensions	26 x 76 mm, thickness 0,9-1,2 mm
Weight	64 kg (141 lb)
Dimensions	75,5 cm (W) 29,7 Inch 32,5 cm (D) 12,8 Inch 62,5 cm (H) 24,6 Inch

Solvent Xylene

Tape KP-Tape (cat# 3020)
width 24 mm, length 70 m

Slide racks cap. 20

Also available special designed slide racks for only 5 slides
All slide racks are compatible to fit all major staining instruments



Supply Model 1: 220 V~ ±10%, 50-60 Hz, 2A
Model 2: 110 V~ ±10%, 50-60 Hz, 3A

CE

SPECIAL FEATURES CM1260

- MULTILINGUAL TOUCH SCREEN
- EASY OPERATION
- PARAMETER SETTING
- AUTOMATED SLIDE DRYING
- HIGH OUTPUT
- SELF SHARPENING KNIFE
- INTEGRATED FUME EXTRACTION
- LOW MAINTENANCE
- SENSOR CONTROLLED PROCESS
- EXCESSIVE XYLENE COLLECTION
- RELIABLE

CONTACT YOUR LOCAL REPRESENTATIVE
FOR MORE INFORMATION OR A
DEMONSTRATION ON-SITE:



KLINIPATH BV
P.O. Box 195
6920 AD Duiven
The Netherlands

T: +31(0)316-266466
F: +31(0)316-266777
E: info@klinipath.nl
I: www.klinipath.nl